

CCU10A231WNI6X

indoor

> CONTATTACI



The CCU series wall-mounted cooling units represent an ideal solution for cooling electrical panels in high external temperatures, isolating them from the surrounding environment. The range of cooling units meets different indoor and outdoor application needs, ensuring high technical and safety standards. In all models, the polyurethane gasket is laid by machine, significantly reducing installation times.

Technical data		
APPROVALS		
Approvals	CE; UKCA	
PERFORMANCE		
Cooling Capacity L35L35	1015/1115	W
	3463/3805	BTU/h
Cooling Capacity L35L50	815/855	W
	2781/2917	BTU/h
ELECTRICAL DATA		
Rated Voltage	230	V a.c.
Rated Current	4.2/4.6	A
Rated Power L35L35	485/565	W
Rated Power L35L50	535/645	W
Frequency	50/60	Hz
Max Current	20	A
Fuse T	8	A
GENERIC DATA		
Weight	40.00	Kg
	88.18	lb
Casing Material	Stainless Steel	AISI 316
Electrical Connection	Connector	
Refrigerant Number	R513A	
Refrigerant Charge	550	

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.

CCU10A231WNI6X

indoor

> CONTATTACI

CLIMATE CONTROL SYSTEMS

Technical data		
GWP	631	
CO2e	0.35	t
Maximum Allowable Pressure	HP 2.4/LP 0.6	MPa
ENVIRONMENTAL AND THERMAL DATA		
Protection Degree Enclosure Side	IP54	
Operating Temperature	20÷50	°C
	68÷122	°F

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.

CCU10A231WNI6X

indoor

> CONTATTACI

CLIMATE CONTROL SYSTEMS

Technical drawing mm (in)

Cooling Capacity vs Temperature

Cooling Capacity vs Temperature

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.