

CCU15A231WNIUX

indoor

> CONTATTACI



The CCU series wall-mounted cooling units represent an ideal solution for cooling electrical panels in high external temperatures, isolating them from the surrounding environment. The range of cooling units meets different indoor and outdoor application needs, ensuring high technical and safety standards. In all models, the polyurethane gasket is laid by machine, significantly reducing installation times.

Technical data		
APPROVALS		
Approvals	CE; UKCA	
PERFORMANCE		
Cooling Capacity L35L35	1415/1555	W
	4828/5306	BTU/h
Cooling Capacity L35L50	1135/1185	W
	3873/4043	BTU/h
ELECTRICAL DATA		
Rated Voltage	230	V a.c.
Rated Current	5.2/5.8	A
Rated Power L35L35	655/755	W
Rated Power L35L50	755/915	W
Frequency	50/60	Hz
Max Current	24	A
Fuse T	8	A
GENERIC DATA		
Casing Material	Painted Steel	
RAL Number	7035	
Electrical Connection	Connector	
Refrigerant Number	R134a	
Refrigerant Charge	520	g
Maximum Allowable Pressure	HP 2.4/LP 0.6	MPa

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities cla

CCU15A231WNIUX

indoor

> CONTATTACI

CLIMATE CONTROL SYSTEMS

Technical data		
ENVIRONMENTAL AND THERMAL DATA		
Protection Degree Internal Circuit	IP54	
Operating Temperature	20÷50	°C
	68÷122	°F

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities cla

CCU15A231WNIUX

indoor

> CONTATTACI

CLIMATE CONTROL SYSTEMS





Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities cla

CCU15A231WNIUX

indoor

> CONTATTACI

Cooling Capacity vs Temperature



Cooling Capacity vs Temperature




Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities cla