standard with fan

> CONTACT US



FF series exhaust filter and filter fans represents a side-mounted cooling solution with filtered ambient air to maintain optimum ventilation inside the electrical cabinets. Screwless connection, fast tool-free mounting system with clip and maintenance friendliness are the main benefits. Available in a wide range of configurations for both indoor and outdoor use.

Technical data		
APPROVALS		
Approvals	CE; UKCA	
PERFORMANCE		
Max Airflow	107	m³/h
	63	CFM
Airflow with Exhaust Filter	70	m³/h
	41	CFM
Max Static Pressure	164	Pa
	0.66	in H2O
ELECTRICAL DATA		
Rated Voltage	24	V d.c.
Rated Current	0.969	А
Rated Power	23	W
Operating Voltage	18-27.6	V d.c.
Motor Protection	Electronically Protected	
MECHANICAL DATA		
Mounting Wall Thickness	1.3-3.2	mm
	0.05-0.13	in
Bearing	Ball Bearing	
GENERIC DATA		
Spare Parts Filter Media	M12FPF-EU3	
Casing Material	PC/ABS UL94 V-0	



FF12D24UN4

standard with fan


> CONTACT US


Technical data			
RAL Number	7035		
Life Expectancy	100000	h at 25 °C	
	100000	h at 77 °F	
Airflow Direction	Direct		
Electrical Connection	Screwless Terminal Block		
Wires Section	0.75-2.5	mm²	
Wires Section	20-14	AWG	
Fan Noise	59.5	dB(A)	
Filter Class	G3	EN 779	
Filter Class	ISO coarse 55%	ISO 16890	
Filter Material	thermo-linked progressive structure synthetic fibre		
ENVIRONMENTAL AND THERMAL DATA			
IP Protection Degree	IP54		
On exeting Temperature	-10÷60	°C	
Operating Temperature	14÷140	°F	
Storage Temperature	-40÷70	°C	
	-40÷158	°F	



standard with fan

> CONTACT US







FF12D24UN4

standard with fan

> CONTACT US

