standard with fan

> CONTACT US



FPF series exhaust filter and filter fans represents a side-mounted cooling solution with filtered ambient air to maintain optimum ventilation inside the electrical cabinets. These units have a flat external profile and a quick snap-on fastening system with elastic hooks. Available in different range of sizes, airflow ratings and configurations.

Technical data		
APPROVALS		
Approvals	CE; cURus; UKCA	
PERFORMANCE		
Max Airflow	23/30	m³/h
	14/18	CFM
Max Static Pressure	42/62	Pa
	0.17/0.25	in H2O
ELECTRICAL DATA		
Rated Voltage	115	V a.c.
Rated Current	0.115/0.092	А
Rated Power	9/7	W
Operating Voltage	103.5-126.5	V a.c.
Frequency	50/60	Hz
Appliance Class	1	
Motor Protection	Impedance Protected	
MECHANICAL DATA		
Mounting Wall Thickness	1.5-2.2	mm
	0.06-0.09	in
Bearing	Ball Bearing	
GENERIC DATA		
Spare Parts Filter Media	M08FPF	
RAL Number	7035	



standard with fan


> CONTACT US


Technical data			
Life Expectancy	50000	h at 20 °C	
	50000	h at 68 °F	
Airflow Direction	Direct		
Electrical Connection	Wires		
Wires Section	22	AWG	
Fan Noise	33/38	dB(A)	
Filter Class	G3	EN 779	
Filter Class	ISO coarse 55%	ISO 16890	
Filter Material	thermo-linked progressive structure synthetic fibre		
Cable Length	300	mm	
	11.81	in	
ENVIRONMENTAL AND THERMAL DATA			
IP Protection Degree	IP54		
Operating Temperature	-10÷50	°C	
	14÷122	°F	
Storage Temperature	-40÷70	°C	
	-40÷158	°F	
UL DATA			
UL File Number Recognized Component	E237844		
UL Environmental Type Rating	Type 12		
UL Ambient Temperature	50	°C	
	122	°F	



standard with fan

> CONTACT US







standard with fan

> CONTACT US

