heaters with cable metal cover

> CONTACT US



Fandis PTC heaters are used for warming up the air inside enclosure, protecting electrical and electronic components from condensation and corrosion. These H series PTC heaters with cable connection are available in two versions: in metal or plastic, with low surface thermal conductivity to keep safe maintenance operations.

Technical data			
APPROVALS			
Approvals	CE; cURus; UKCA		
PERFORMANCE			
Heating Power	5	W	
ELECTRICAL DATA			
Rated Voltage	110-240	V a.c./d.c.	
Operating Voltage	99-264	V a.c.	
Frequency	50/60	Hz	
Max Current	1.1	А	
Appliance Class	1		
GENERIC DATA			
Casing Material	Black Anodised Aluminium		
Electrical Connection	Wires		
Wires Section	20	AWG	
Cable Length	500	mm	
	19.68	in	
Fixing System	DIN rail		
ENVIRONMENTAL AND THERMAL DATA			
IP Protection Degree	IP20		
Operating Temperature	-30÷50	°C	
	-22÷122	°F	



HWM005 heaters with cable metal cover

> CONTACT US


Technical data			
Storage Temperature	-40÷70	°C	
	-40÷158	°F	
UL DATA			
UL File Number Recognized Component	E237844		
UL Environmental Type Rating	Open Type		
UL Ambient Temperature	50	°C	
	122	°F	




HWM005

heaters with cable metal cover

> CONTACT US







HWM005

heaters with cable metal cover

> CONTACT US

