TP19U1 | standard without fan

TP series roof exhaust units represent an optimal solution for heat dissipation through the top of electrical cabinets. They are ideal for indoor use where there is limited space on the front and side panels. According to the ambient conditions these units can operated with fan (forced air) or without a fan (natural air convection).

| Technical data		
APPROVALS		
Approvals	CE; cURus; cULus; cCSAus; UKCA	
GENERIC DATA		
Weight	1.14	Kg
	2.52	lb
RAL Number	7035	
ENVIRONMENTAL AND THERMAL DATA		
IP Protection Degree	IP24	
Operating Temperature	-10÷60	°C
	14÷140	°F
Storage Temperature	-45÷75	°C
	-49÷167	°F
UL DATA		
UL File Number Recognized Component	E237844	
UL File Number Listed	E500932	
UL Environmental Type Rating	Type 12	
UL Ambient Temperature	55	°C
	131	°F

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities cla

TP19U1 | standard without fan

> CONTATTACI

Technical drawing mm (in)

324 (12.76)

324 (12.76)

94 (3.70)

62 (2.44)

219 (8.62)

Mounting cut-out mm (in)

189 (7.44)

175 (6.89)

78 (3.07)

189 (7.44)

175 (6.89)

78 (3.07)

Ø 5 (Ø 0.197)

Fandis

TP19U1 | standard without fan

> CONTATTACI

Air Performance

Air Flow **[CFM]**

| 0.0 | 58.9 | 117.8 | 176.6 | 235.5 | 294.4 | 353.3 | 412.1 | 471.0 |

Static Pressure **[Pa]** (left axis): 0, 60, 120, 180, 240, 300, 360, 420, 480, 540

Static Pressure **[inH2O]** (right axis): 0.00, 0.24, 0.48, 0.72, 0.96, 1.21, 1.45, 1.69, 1.93, 2.17

Air Flow **[m3/h]** (bottom axis): 0, 100, 200, 300, 400, 500, 600, 700, 800

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities cla