OF-A12R12HWBWQ135

AC orientable fan

 $> \ensuremath{\mathsf{CONTACT}}\xspace$ US

Indacus



The swivelling fans can be adjusted to cool down particularly hot spots and ensure a good distribution of air inside the electrical panel. It was designed together with a metal support to facilitate installation in vertical or horizontal positions, depending on the need.

Technical data		
APPROVALS		
Approvals	CE; UKCA	
PERFORMANCE		
Max Airflow	141/178	m³/h
	83/105	CFM
Max Static Pressure	62/75	Pa
	0.25/0.30	in H2O
RPM	2650/2950	RPM
ELECTRICAL DATA		
Rated Voltage	115	V a.c.
Rated Current	0.22/0.2	A
Rated Power	20/18	W
Operating Voltage	85-125	V a.c.
Frequency	50/60	Hz
Appliance Class	Ι	
Insulation Class	A	
Motor Protection	Impedance Protected	
MECHANICAL DATA		
Bearing	Ball Bearing	
GENERIC DATA		
Casing Material	Die-Casting Aluminium	
Airflow Direction	Air intake over brackets	

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.



OF-A12R12HWBWQ135

AC orientable fan

 $> \ensuremath{\mathsf{CONTACT}}\xspace$ US

Technical data			
Electrical Connection	Screwless Terminal Block		
Fan Noise	46/49	dB(A)	
Fixing System	Screws		
ENVIRONMENTAL AND THERMAL DATA			
IP Protection Degree	IP20		
Operating Temperature	-10÷60	°C	
	14÷140	°F	
Storage Temperature	-40÷70	°C	
	-40÷158	°F	

Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.



Indacus

OF-A12R12HWBWQ135

AC orientable fan

 $> \ensuremath{\mathsf{CONTACT}}\xspace$ US



Image is for illustrative purpose only. All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.

